

DTIC FILE COPY

4

AD-A202 989

COMPARISON OF SINGLE GRADE AND MULTIVISCOSITY LUBRICANTS IN M60 TANKS UNDER HOT AMBIENT CONDITIONS

INTERIM REPORT
BFLRF No. 240

By

A.F. Montemayor
E.C. Owens

Belvoir Fuels and Lubricants Research Facility (SwRI)
Southwest Research Institute
San Antonio, Texas

Under Contract to

U.S. Army Belvoir Research, Development
and Engineering Center
Materials, Fuels and Lubricants Laboratory
Fort Belvoir, Virginia

Contract No. DAAK70-87-C-0043

Approved for public release; distribution unlimited

DTIC
ELECTE
DEC 20 1988
S H D

May 1988

88 12 20 077

ADA202989

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS None		
2a. SECURITY CLASSIFICATION AUTHORITY N/A			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) Interim Report BFLRF No. 240			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION Belvoir Fuels and Lubricants Research Facility (SwRI)		6b. OFFICE SYMBOL (If applicable)		7a. NAME OF MONITORING ORGANIZATION	
6c. ADDRESS (City, State, and ZIP Code) Southwest Research Institute San Antonio, Texas 78284				7b. ADDRESS (City, State, and ZIP Code)	
8a. NAME OF FUNDING/SPONSORING ORGANIZATION U.S. Army Belvoir Research, Development and Engineering Center		8b. OFFICE SYMBOL (If applicable) STRBE-VF		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER DAAK70-85-C-0007, WD 11; DAAK70-87-C-0043, WD 5	
8c. ADDRESS (City, State, and ZIP Code) Fort Belvoir, VA 22060-5606		10. SOURCE OF FUNDING NUMBERS			
		PROGRAM ELEMENT NO. 263001		PROJECT NO. IL26300 ID150	TASK NO. 07(1)
				WORK UNIT ACCESSION NO.	
11. TITLE (Include Security Classification) Comparison of Single-Grade and Multiviscosity Lubricants in M60 Tanks Under Hot Ambient Conditions (U)					
12. PERSONAL AUTHOR(S) Montemayor, A.F. and Owens, Edwin C.					
13a. TYPE OF REPORT Interim		13b. TIME COVERED FROM Aug 87 to Aug 88		14. DATE OF REPORT (Year, Month, Day) 1988 August	
15. PAGE COUNT 45					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Comparison, Atmospheric Temperature, Lubricating Oils, Lubricants, Tank Engines, Pressure, High Temperature Engines, Low Pressure. JET		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>In this program, two MIL-L-2104D lubricants, OE/HDO-15/40 and OE/HDO-40, and one SAE 50-grade lubricant were evaluated in three M60A2 RISE passive tanks. The tanks, with AVDS-1790-2C engines, were used to evaluate these lubricants under high ambient temperature conditions. As a result of this program, no significant differences in engine oil operating temperatures were found between the MIL-L-2104D 15W-40 or 40 grades and the SAE 50-grade lubricants. Although significant differences were noted in operating temperatures among vehicles, these differences were larger than any observed oil differences.</p> <p>In addition, no difference was noted in idle oil pressure between the OE/HDO-40 and the SAE 50-grade lubricants in fully warm engines. It was noted that the OE/HDO-15/40 oil produced approximately 1-psi lower oil pressure at idle than the SAE 50 grade in fully warm engines. However, engine-to-engine difference in idle oil pressure was larger than the oil viscosity-related differences.</p>					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Mr. T.C. Bowen		22b. TELEPHONE (Include Area Code) (703) 664-3576		22c. OFFICE SYMBOL STRBE-VF	

FOREWORD

This work was performed at the Belvoir Fuels and Lubricants Research Facility (BFLRF) located at Southwest Research Institute (SwRI), San Antonio, TX, under Contract Nos. DAAK70-85-C-0007 and DAAK70-87-C-0043, for the period 24 August 1987 through 28 August 1988. Work was funded by the U.S. Army Belvoir Research, Development and Engineering Center (Belvoir RDE Center), Ft. Belvoir, VA. Mr. T.C. Bowen, Belvoir RDE Center (STRBE-VF), was the contracting officer's representative, and Mr. M.E. LePera was the technical monitor.

Accession For
 A112 GRA&I
 DTIC 100
 DTIC 100
 DTIC 100
 DTIC 100

ACKNOWLEDGEMENTS

The authors wish to express appreciation to the personnel from The Marine Corps Air Ground Combat Training Center at Twenty-Nine Palms, CA, for the excellent cooperation and professionalism displayed during this project. The authors also gratefully acknowledge the conduct and interpretation of the statistical analyses provided by Ms. Janet Buckingham of Southwest Research Institute.

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
I. BACKGROUND	1
II. OBJECTIVE	1
III. SCOPE	1
IV. APPROACH	2
V. DISCUSSION OF RESULTS	5
VI. CONCLUSIONS	11
VII. RECOMMENDATIONS	12
VIII. LIST OF REFERENCES	12
APPENDICES	
A. Edited Data	15
B. Lubricant Analyses	43

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
1 Lubricant Viscosity Comparison	2
2 Location of Oil Gallery Pressure and Temperature Tap	3
3 Oil Sump Temperature Versus Time Relationships for Vehicle No. 1	7
4 Oil Sump Temperature Versus Time Relationships for Vehicle No. 3	7
5 Oil Sump Temperature Versus Time Relationships for Vehicle No. 2	8
6 Idle Oil Pressure	9
7 Idle Oil Pressure	9
8 Idle Oil Pressure by Vehicle	10

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1 Test Matrix	4
2 Average Ambient Air Temperature for Each Test Run, °F (°C)	6
3 Engine Oil Iron Generated During Each Test	11

I. BACKGROUND

Military Specification MIL-L-2104D was recently amended to specify a grade 15W-40 (military symbol OE/HDO-15/40) lubricant for use in combat and tactical equipment.(1)* This multigrade oil would help eliminate seasonal oil changes and simplify logistics. Extensive testing of the multiviscosity lubricants has revealed no significant field problems.(2,3) Along with the other specification revisions, the OE/HDO-50 (grade 50) oil was eliminated. The use of this viscosity grade had fallen to a low level, and it was believed that the 15W-40 or 40 grades were acceptable substitutes. The 40 grade was retained because of a requirement of some stationary engines.

Engine overheating, final drive seal leakage, and short engine life when using OE/HDO-15/40 oil were reported in the M60 battle tanks by the U.S. Marine Corps during the summer of 1986. As a result, the Marine Corps expressed concern about the adequacy of the OE/HDO-15/40 product to protect the AVDS-1790-2C engine used in the M60 tanks, particularly under high-temperature/high-load conditions. A program to investigate these complaints was authorized by the U.S. Army Belvoir Research, Development and Engineering Center (Belvoir RDE Center).

II. OBJECTIVE

The objective of this program was to compare the performance of the MIL-L-2104D OE/HDO-15/40, OE/HDO-40, and a commercially available SAE 50-grade lubricant in M60 tanks under high ambient temperature conditions.

III. SCOPE

Two MIL-L-2104D lubricants, OE/HDO-15/40 and OE/HDO-40, and one SAE 50-grade lubricant were evaluated in this program. Three M60A2 RISE passive tanks with AVDS-1790-2C engines were used to evaluate these lubricants under high ambient temperature conditions during 24 August 1987 through 28 August 1987.

* Underscored numbers in parentheses refer to the list of references at the end of this report.

IV. APPROACH

Belvoir Fuels and Lubricants Research Facility (BFLRF) at Southwest Research Institute (SwRI) procured and shipped two 55-gallon drums each of the OE/HDO-15/40 and OE/HDO-40 lubricants to the Marine Corps Air Ground Combat Center at Twenty-Nine Palms, CA. The 50-grade oil was that currently in use at Twenty-Nine Palms. Analyses of the test oils are given in Appendix A. Fig. 1 illustrates the viscosity of the three oils at both 40° and 100°C.




Figure 1. Lubricant viscosity comparison

Three M60A1 RISE passive tanks were chosen for testing. These tanks were C25, C21, and C22 henceforth referred to as vehicle Nos. 1, 2, and 3, respectively. Each tank was equipped with the AVDS-1790-2C RISE engine. The power packs were pulled from each vehicle, the oil coolers pressure cleaned, the oil changed, and the power packs reinstalled. The oil coolers were not drained. A 4-fluid-ounce sample of the lubricant was drained from each vehicle. The engine access panel, located in the rear of the crew compartment, was removed in order to provide access to the engine from the turret area. The panel remained off during the testing.

Each engine was instrumented to record oil sump temperature, oil gallery temperature, ambient air temperature, engine compartment temperature, and oil pressure. The oil sump temperatures were obtained by fastening exposed junction type T thermocouples to the oil dipsticks of each engine with stainless steel tie wire. The oil gallery temperatures were obtained by replacing the 3/4-in. (19.05-mm) pipe plugs (see Fig. 2) with T-fittings for thermocouple and pressure taps. The ungrounded type T thermocouples were inserted until they touched the springs in the oil galleries and then withdrawn 0.25 inch (6.35 mm).




Figure 2. Location of oil gallery pressure and temperature tap

Ambient temperatures were obtained by wiring thermocouples to the outside of the turrets near the gunners' hatchways. To minimize direct solar heat on the thermocouples, they were shielded along their length and on top by a Teflon® tube so that only the lower tips of the thermocouples were exposed. In practice, however, solar impingement on the turrets directly under the thermocouples raised the actual recorded temperatures when the tanks were at rest. The engine compartment thermocouples were tie wrapped

to the right protector bars located just inside the access panel and adjacent to the 3/4-in. (19.05 mm) pipe plugs. It was hoped that this position would indicate the engine compartment temperature. In practice, however, air was pulled into the engine compartments through the open access panels, and the recorded temperatures were more representative of the crew compartments than the normal engine compartment. Oil pressures were obtained from the T-fittings, through 1/4-in. (6.35-mm) hoses, and thence to 0- to 200-psig pressure transducers. All signals were routed to data loggers secured on the oddment racks in the turrets of each vehicle. The data loggers were preprogrammed to log each of the variables once per minute and to record the time of day and internal battery voltages. The thermocouples and pressure transducers were previously checked in conjunction with the data logger for reading accuracy. The thermocouples were accurate to $\pm 2.2^{\circ}\text{F}$ when checked at 212°F (100°C), and the pressure transducers were accurate to ± 0.7 psig over the range of 0 to 60 psig.

Testing of the vehicles started at approximately 1:00 pm each day in order to obtain the hottest ambient temperatures for the test. The vehicles were run under a variety of conditions, including idling, hill climbing, high-speed road, and slow march. Terrain for the testing was desert sand with low hills. The test course was to have been the same for all three days of testing. In reality, however, the terrain had minor variations, particularly on the first day. At the completion of each run, the oil was drained (in hull), and the next test oil introduced into the engines. Although the oil filters were changed, the oil coolers were not drained. Again, 4-fluid-ounce samples of the drained lubricants were taken. Since the oil coolers were not drained, it was recognized that there would be some undrained lubricant carryover mixed with the test oils. A schedule of the tests performed is shown in TABLE 1.

TABLE 1. Test Matrix

	Vehicle		
	No. 1	No. 2	No. 3
Run No. 1	SAE 50	OE/HDO-40	OE/HDO-15/40
Run No. 2	OE/HDO-40	OE/HDO-15/40	SAE 50
Run No. 3	OE/HDO-15/40	SAE 50	OE/HDO-40

V. DISCUSSION OF RESULTS

During the testing, four notable anomalies occurred. Vehicle No. 1 (SAE 50) incurred a minor problem that forced termination of testing in that vehicle during the first day of testing. The malfunction ended testing with that vehicle before the oil temperatures reached their maximums. The vehicle was towed to the maintenance facility. On day 2, vehicle No. 2 (OE/HDO-15/40), oil pressure maximums were abnormally low. Although idle oil pressures were normal, oil pressure maximums never exceeded 41 psig; 50- to 55-psig oil pressures would be normal. In addition, the oil temperature drop across the coolers was abnormally high for this run. These observations are believed to indicate a low oil sump level, although no mention of a low oil sump level was made by crew members. There was one sensor failure during the testing. The oil sump thermocouple failed on vehicle No. 2, day 3, (SAE 50) after only a few minutes of running. Vehicle No. 1, day 3, also had 4 minutes of ambient air temperature not being recorded. A connector, which had separated, was simply reconnected, and the data recording continued.

Edited data are shown in Appendix A. In the appendix, pre- and post-test data have been eliminated, and missing values have been replaced with question marks. The first column indicates the number of minutes past noon. The raw data show that ambient air temperatures rose significantly during idle periods. This increase in temperature is probably caused by radiant and convective heating from the stationary turrets, producing a higher reading on the thermocouple than the actual air temperature. When the vehicle began moving, the temperatures decreased to actual air temperatures. Recorded temperatures remained high briefly after idles as the vehicles began to accelerate. In order to compensate for this aberration, ambient air temperatures at idle and for 1 minute after idles were changed to missing values. All analyses were done using the edited data.

Average ambient air temperatures were 98.2° (36.8°) to 102.9°F (39.4°C) during the testing. Average ambient air temperatures for each test run are shown in TABLE 2. These temperatures exclude pre- and post-test data and idle data as previously described.

TABLE 2. Average Ambient Air Temperature for Each Test Run, °F (°C)

	Vehicle		
	No. 1	No. 2	No. 3
Run No. 1	101.0 (38.0)	99.6 (37.6)	100.2 (37.9)
Run No. 2	98.2 (36.8)	99.4 (37.4)	100.9 (38.3)
Run No. 3	100.7 (38.2)	100.3 (37.9)	102.9 (39.4)

Oil sump temperature versus time relationships for vehicle Nos. 1 and 3 are shown in Figs. 3 and 4. Note that in Fig. 3 (vehicle No. 1), the curve for the SAE-50 oil is abbreviated due to the mechanical failure of the vehicle. A similar comparison for vehicle No. 2 is given in Fig. 5, although without the SAE-50 data due to the previously noted sensor failure. Comparison of the oil sump temperatures for vehicle No. 1 using the three grades of oil seems to indicate that the OE/HDO-15/40 lubricant produced slightly higher temperatures than the OE/HDO-40 or SAE-50 products. This conclusion is difficult to support, however, since vehicle No. 1 never reached peak operating temperatures with the SAE-50 lubricant. The OE/HDO-15/40 lubricant produced the same or lower sump temperatures in vehicle Nos. 2 and 3. Oil gallery temperature comparisons also showed this same pattern.

Engine oil pressure is a function of engine speed, engine wear (both in the bearings and pump), and oil viscosity. Maximum oil pressures are limited by either relief valves or the ability of the pump to deliver oil. Minimum oil pressures are limited by the ability of the pump to deliver oil and the viscosity of the oil. The engine oil pressure at idle then should be directly related to the oil viscosity and the sump oil temperature. It would be expected that higher viscosity grade oils would produce higher idle oil pressures, since the temperature data had shown no differences in oil temperatures. The primary question to be answered is how much difference is there between grades, and is this difference likely to impact vehicle durability?

Note that all the test vehicles had idle oil pressures below the 15-psi minimum level recommended by the engine manufacturer, except for vehicle No. 1 on day 1 when the engine failed before reaching fully warmed conditions. No engine warning lights were noted by the crews.




Figure 3. Oil sump temperature versus time relationships for vehicle No. 1




Figure 4. Oil sump temperature versus time relationships for vehicle No. 3




Figure 5. Oil sump temperature versus time relationships for vehicle No. 2

Data from periods in which the engines were at idle were extracted from the oil pressure and sump oil temperature data sets. As expected, as the oil temperature increased, the idle oil pressure fell. This decrease is illustrated in Fig. 6 in the data from vehicle No. 1. At sufficiently high temperatures, the idle pressure with each of the different viscosity grades became very close.

In order to compare the idle oil pressures across the vehicles and viscosity grades, the temperatures above 190°F (88°C) were selected. These pressures were assumed to most closely represent fully warmed engine conditions. Figs. 6 and 7 show 95-percent Tukey intervals for the means of the idle oil pressure by both oil type and by vehicle. This statistical approach attempts to account for day-to-day differences. The lubricants are ranked in the expected order of increasing oil pressure from 15W-40 to 50 grade.

Overlapping of the bands between the lubricants indicates that there may be no statistical difference between the OE/HDO-15/40 and the OE/HDO-40 nor between the OE/HDO-40 and the OE/HDO-50 products. There appears to be a statistical difference between the OE/HDO-15/40 and the OE/HDO-50 lubricants. The difference between the




Figure 6. Idle oil pressure
(Vehicle No. 1)




Figure 7. Idle oil pressure
(190° to 240°F)

two lubricants is approximately 1 psig. The vehicle-to-vehicle differences were larger, with the range between the vehicle Nos. 1 and 3 being about 3 psig.

These data indicate that under fully warmed conditions, there are small differences in idle oil pressure between any of the oils tested. The vehicle-to-vehicle differences (build clearances, wear, etc.) caused larger differences in idle oil pressure. Under some types of operations, however, there may be larger differences in idle oil pressure between the various oil grades. As shown in Fig. 8, as the vehicle begins to cool down at idle, the oil pressure begins to rise as the oil viscosity increases. Under this condition, both the straight grade oils recover oil pressure faster than the multiviscosity OE/HDO-15/40 (assuming equal cooling rates). There may be some types of operations where this faster recovery could have an impact on bearing wear.




Figure 8. Idle oil pressure by vehicle
(All oils)

Appendix B shows selected properties on the existent, new, and used oils. Based on the iron content of the used oils, and assuming that the new oil had no iron in it, the quantity of unchanged oil remaining in the coolers averages 36 percent of the total oil capacity. This residue was undesirable, but unavoidable since draining the coolers required removal

of the engines. Using the 36-percent residue figure, and averaging the XRF and ICP iron analyses, the amount of iron generated during each test is shown in TABLE 3.

TABLE 3. Engine Oil Iron Generated During Each Test

	Vehicle		
	No. 1	No. 2	No. 3
Run No. 1	-1 ppm (50 gr.)	16 ppm (40 gr.)	3 ppm (15W-40 gr.)
Run No. 2	20 ppm (40 gr.)	9 ppm (15W-40 gr.)	19 ppm (50 gr.)
Run No. 3	6 ppm (15W-40 gr.)	10 ppm (50 gr.)	13 ppm (40 gr.)

The -1 value for vehicle No. 1, run No. 1, indicates that iron content decreased during the test and resulted from minor inaccuracies in the measurement or sampling technique. The SAE-50 product averaged a 13-ppm increase, the OE/HDO-40 product averaged a 16-ppm increase, and the OE/HDO-15/40 product averaged a 6-ppm increase.

The used oil analyses show that vehicle No. 3 initially had higher iron, lead, copper, and silicon levels than the other vehicles. These higher levels indicate that vehicle No. 3 had either more miles of operation since oil change than the other vehicles, or was wearing at a more rapid rate than the others or both. Vehicle No. 3 consistently maintained higher iron, lead, and copper levels than the other vehicles, indicating accelerated wear in this vehicle. This accelerated wear in vehicle No. 3 may have been caused by the consistently higher temperatures exhibited by the vehicle.

VI. CONCLUSIONS

- There were no significant differences in engine oil operating temperatures between the MIL-L-2104D 15W-40 or 40 grades and the SAE 50-grade lubricants.
- There were significant differences in operating temperatures among vehicles. These differences were larger than any observed oil differences.
- There was no difference in idle oil pressure between the OE/HDO-40 and the SAE 50-grade lubricants in fully warm engines.

- The OE/HDO-15/40 oil produced approximately 1-psi lower oil pressure at idle than the SAE 50 grade in full warm engines.
- The engine-to-engine difference in idle oil pressure was larger than the oil viscosity-related differences.
- Although idle oil pressures as low as 9 psi were recorded during the testing, no oil pressure warning lights were activated, indicating the activation levels for these warning lights are set considerably below the 15-psi levels called for in the technical manuals.

VII. RECOMMENDATIONS

- Data should be developed on engine oil pressure versus wear. This information would be of value in current and future lubricant development programs.
- The possibility of increased bearing wear during high-temperature operations should be investigated further. In particular, testing needs to be conducted in operations where the vehicles are brought to high temperatures, then idled repeatedly. This type of run-heat-run cycle is common under some combat scenarios.
- This program did not address engine wear directly, and does not provide any significant data on wear. Although laboratory testing has not shown any wear problems with the 15W-40 grade in the AVDS-1790-2C engine, if further testing is undertaken, this aspect should be included.

VIII. LIST OF REFERENCES

1. U.S. Military Specification MIL-L-2104E, "Lubricating Oil, Internal Combustion Engine, Tactical Service," 1 August 1988.
2. Butler, Jr., W.E.; Owens, E.C.; Frame, E.A.; and Bowen, T.C., "Pilot Field Tests of Multiviscosity/Synthetic Engine Oil in Army Combat Tactical Vehicles at Ft. Bliss, TX," Interim Report AFLRL No. 160, AD A134703, prepared by U.S. Army Fuels and Lubricants Research Laboratory, San Antonio, TX, July 1982.

3. Butler, Jr., W.E.; Alvarez, R.A.; Frame, E.A.; Buckingham, J.P.; and Owens, E.C., "Field Evaluation of All-Season Tactical Engine Oil OE/HDO 15W-40 at Ft. Knox, KY and Ft. Bliss, TX," Interim Report BFLRF No. 217, prepared by Belvoir Fuels and Lubricants Research Facility (SwRI), San Antonio, TX, July 1986.

APPENDIX A

Edited Data

(NOTE: Question mark in tables indicates a faulty or missing measurement.)

Day 1
M60 Tank No. 1, SAE-50 Lubricant

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
64	1304.	115.1	117.6	?	95.0	56.78
65	1305.	119.9	124.4	101.2	93.4	55.44
66	1306.	123.5	131.4	102.0	93.5	53.34
67	1307.	121.4	132.9	102.5	93.8	52.16
68	1308.	122.2	134.1	102.9	93.8	51.32
69	1309.	139.3	138.7	101.6	93.5	68.32
70	1310.	153.3	144.0	100.0	93.5	65.69
71	1311.	147.7	147.4	101.0	92.9	62.12
72	1312.	140.8	147.2	101.7	93.4	38.34
73	1313.	168.6	151.9	100.1	93.1	67.08
74	1314.	174.6	158.0	99.3	93.3	65.84
75	1315.	187.2	164.9	98.4	93.4	66.41
76	1316.	187.1	171.0	98.8	93.7	63.23
77	1317.	195.3	176.5	100.0	94.1	62.83
78	1318.	199.0	181.3	100.9	94.4	62.50
79	1319.	201.6	184.5	101.3	93.9	49.49
80	1320.	205.5	187.8	101.2	93.8	56.93
81	1321.	210.0	191.4	101.9	94.1	59.28
82	1322.	213.1	195.0	101.3	93.3	58.20
83	1323.	219.0	198.5	101.7	93.7	57.89
84	1324.	219.9	201.6	102.6	94.8	58.28
85	1325.	221.2	203.1	103.0	95.4	59.90
86	1326.	226.7	205.6	101.7	95.1	59.16
87	1327.	229.0	208.8	101.5	94.8	58.75
88	1328.	232.4	211.4	101.9	95.4	48.25
89	1329.	228.0	213.6	102.0	95.1	45.61
90	1330.	231.1	213.0	102.8	96.2	49.41
91	1331.	230.4	212.7	102.2	95.7	53.41
92	1332.	228.4	211.7	102.0	95.9	38.15
93	1333.	228.6	212.3	100.4	95.0	55.78
94	1334.	230.9	212.7	100.3	94.8	44.42
95	1335.	229.8	212.0	100.2	94.9	53.23
96	1336.	224.6	209.9	?	95.5	15.46
97	1337.	219.1	209.9	?	98.9	16.46
98	1338.	217.7	208.8	?	99.3	16.76
99	1339.	215.5	207.0	?	99.0	17.51
100	1340.	220.3	202.4	?	97.7	59.21
101	1341.	224.2	204.2	101.7	95.5	58.81
102	1342.	225.8	207.3	101.3	95.3	61.99
103	1343.	226.4	209.6	101.1	95.9	56.98

Notes: Min in column 1 indicates minutes past noon on the day of each test.
Time is in military format.
All temperatures are degrees Fahrenheit. To convert to degrees
Centigrade, multiply temperature (°F) - 32 by 5/9.
Oil pressure is in psig.

Day 1
M60 Tank No. 1, SAE-50 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
104	1344.	223.5	208.9	?	95.4	16.00
105	1345.	222.1	206.7	?	95.8	16.36
106	1346.	224.2	205.3	?	95.3	50.19
107	1347.	226.5	207.4	98.8	94.8	59.65
108	1348.	227.2	210.5	97.7	94.9	46.36
109	1349.	229.4	210.1	99.1	95.9	54.89
110	1350.	221.7	210.2	?	95.9	17.89
111	1351.	224.0	207.0	?	95.6	52.24
112	1352.	226.8	208.7	99.9	95.7	59.08

Day 1
M60 Tank No. 2, OE/HDO-40 Lubricant

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
64	1304.	109.0	108.0	?	97.3	56.05
65	1305.	111.1	116.6	102.7	93.6	54.13
66	1306.	119.7	123.1	102.2	94.2	51.66
67	1307.	119.8	126.2	101.9	93.4	49.21
68	1308.	120.9	128.0	101.5	93.6	47.83
69	1309.	126.2	133.5	101.1	93.4	66.25
70	1310.	147.0	142.4	99.4	93.8	62.21
71	1311.	151.4	144.2	100.3	93.8	52.15
72	1312.	149.3	145.5	100.9	93.8	31.30
73	1313.	160.4	147.9	99.9	93.8	62.61
74	1314.	172.1	155.3	98.7	93.7	62.73
75	1315.	181.9	162.0	98.3	93.3	61.03
76	1316.	190.3	169.3	98.4	93.5	60.17
77	1317.	198.0	174.5	98.7	94.0	58.30
78	1318.	203.2	179.7	99.3	94.1	57.11
79	1319.	203.8	183.3	100.0	94.3	54.83
80	1320.	208.1	185.1	100.1	93.5	50.64
81	1321.	212.2	188.6	100.1	93.9	51.73
82	1322.	215.3	191.7	100.5	93.8	55.10
83	1323.	220.5	194.9	100.6	93.4	55.01
84	1324.	221.9	197.7	101.4	94.8	45.50
85	1325.	224.3	199.6	101.7	95.1	50.87
86	1326.	227.6	202.0	101.6	95.9	54.38
87	1327.	228.7	205.1	101.2	95.4	51.89
88	1328.	232.8	207.3	101.1	95.6	47.10
89	1329.	231.0	208.4	101.5	96.4	46.62
90	1130.	230.4	208.9	101.5	95.4	45.55
91	1331.	230.2	210.1	101.7	96.5	41.13
92	1332.	230.2	209.6	101.1	95.9	44.28
93	1333.	231.6	208.9	99.5	95.2	42.27
94	1334.	232.2	210.2	99.1	95.3	45.43
95	1335.	232.6	209.8	98.6	95.8	22.72
96	1336.	230.6	208.6	98.8	95.7	36.98
97	1337.	226.6	207.7	?	98.5	13.41
98	1338.	224.6	205.6	?	99.2	13.74
99	1339.	222.2	202.7	?	99.3	14.09
100	1340.	219.5	199.3	?	98.6	51.95
101	1341.	224.6	199.8	101.2	96.3	52.74
102	1342.	228.1	202.6	99.5	96.3	49.51
103	1343.	229.1	205.2	98.8	95.6	46.75

Notes: Min in column 1 indicates minutes past noon on the day of each test.
Time is in military format.
All temperatures are degrees Fahrenheit. To convert to degrees
Centigrade, multiply temperature (°F) - 32 by 5/9.
Oil pressure is in psig.

Day 1
M60 Tank No. 2, OE/HDO-40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
104	1344.	221.1	205.8	?	94.9	13.03
105	1345.	220.3	204.3	?	94.6	13.36
106	1346.	222.1	202.6	?	95.4	13.60
107	1347.	221.6	198.9	?	95.6	48.0
108	1348.	227.1	202.5	98.3	95.3	55.59
109	1349.	229.2	205.1	97.5	94.8	40.63
110	1350.	224.6	206.1	99.5	96.9	56.71
111	1351.	231.9	205.8	99.7	96.0	55.05
112	1352.	227.1	208.3	100.3	96.3	21.70
113	1353.	229.2	206.0	99.4	95.3	52.23
114	1354.	224.1	205.6	100.2	96.4	54.25
115	1355.	229.4	205.6	100.1	95.7	45.22
116	1356.	231.0	207.7	99.7	95.3	37.62
117	1357.	233.2	207.9	98.5	95.4	37.84
118	1358.	228.6	206.4	?	95.9	14.12
119	1359.	226.2	206.2	?	95.5	46.91
120	1400.	225.4	205.1	98.4	95.9	42.70
121	1401.	227.5	206.8	?	95.9	19.11
122	1402.	223.2	204.0	?	96.1	39.55
123	1403.	219.3	201.4	?	96.2	13.16
124	1404.	221.6	202.7	?	97.8	53.94
125	1405.	226.6	200.9	99.4	95.5	26.31
126	1406.	222.3	201.6	99.1	95.7	50.46
127	1407.	218.9	200.1	98.5	95.5	52.00
128	1408.	221.5	198.7	99.1	95.0	56.40
129	1409.	228.2	201.7	98.2	95.1	53.88
130	1410.	220.0	201.7	?	96.9	13.96
131	1411.	217.2	199.5	?	97.2	14.35
132	1412.	215.9	198.1	?	97.3	14.57
133	1413.	214.4	195.8	?	97.4	14.93
134	1414.	212.5	192.2	?	97.2	15.34
135	1415.	210.2	189.4	?	97.6	15.88
136	1416.	204.6	186.8	?	97.2	28.17
137	1417.	203.9	186.8	99.6	96.1	40.09
138	1418.	204.1	186.3	99.4	96.3	55.64
139	1419.	208.4	187.2	98.8	96.3	56.97
140	1420.	213.6	192.4	97.8	96.1	55.27
141	1421.	220.4	197.5	97.9	95.9	51.57
142	1422.	223.7	201.8	97.9	95.7	46.41
143	1423.	227.7	205.9	98.5	96.3	46.96
144	1424.	232.9	209.3	98.1	95.7	48.03
145	1425.	234.5	212.6	98.5	96.0	41.44
146	1426.	238.3	214.8	98.6	96.3	40.11
147	1427.	239.1	216.2	98.2	96.0	33.21
148	1428.	243.0	219.0	98.5	96.5	42.33

Day 1
M60 Tank No. 2, OE/HDO-40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
149	1429.	245.4	220.9	98.3	96.2	42.62
150	1430.	245.3	221.8	?	95.9	11.19
151	1431.	242.0	219.5	?	96.4	42.29
152	1432.	240.7	217.7	99.0	97.1	43.09
153	1433.	239.8	217.6	98.9	96.6	35.89
154	1434.	242.2	217.2	98.9	96.7	39.29
155	1435.	242.4	216.9	98.2	96.7	44.61
156	1436.	240.2	217.9	98.0	96.6	22.39
157	1437.	238.3	216.0	99.4	97.5	33.08
158	1438.	237.9	215.5	99.0	97.0	32.94
159	1439.	236.7	215.7	?	97.5	11.34
160	1440.	233.9	213.9	?	98.6	21.56
161	1441.	232.4	211.7	100.8	97.9	44.90
162	1442.	230.4	208.6	?	97.3	13.08
163	1443.	228.7	205.2	?	98.2	45.92
164	1444.	221.7	201.5	?	98.8	13.89
165	1445.	219.1	198.3	?	99.3	14.59

Day 1
M60 Tank No. 3, OE/HDO-15/40 Lubricant

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
65	1305.	112.2	113.3	?	93.4	36.63
66	1306.	119.6	120.3	105.2	92.6	47.54
67	1307.	119.9	122.9	105.4	93.4	45.69
68	1308.	122.2	125.0	105.8	93.4	45.20
69	1309.	128.3	129.8	105.7	92.6	51.05
70	1310.	147.7	143.1	102.8	93.1	52.21
71	1311.	150.9	150.2	100.2	93.2	32.26
72	1312.	157.8	154.3	99.0	93.3	29.97
73	1313.	163.1	155.4	97.6	93.6	50.54
74	1314.	173.1	163.8	96.2	93.4	53.07
75	1315.	182.2	170.9	95.2	92.8	50.66
76	1316.	193.6	176.5	94.8	93.3	52.17
77	1317.	197.4	181.5	95.1	94.3	50.34
78	1318.	202.6	184.2	95.2	94.4	37.23
79	1319.	206.6	187.4	95.1	93.8	43.49
80	1320.	211.0	190.5	94.9	94.0	28.15
81	1321.	211.9	194.5	94.8	94.4	51.58
82	1322.	213.5	196.2	95.3	94.1	52.35
83	1323.	215.7	199.6	97.3	93.6	49.42
84	1324.	221.0	202.8	98.3	93.1	50.71
85	1325.	223.7	205.0	99.0	93.8	45.67
86	1326.	228.7	207.2	99.5	93.9	23.07
87	1327.	225.8	210.0	100.5	93.9	28.87
88	1328.	232.9	212.2	100.7	95.0	44.74
89	1329.	235.1	213.8	99.9	95.2	48.71
90	1330.	234.9	215.0	101.4	95.4	32.01
91	1331.	236.1	215.3	101.8	95.5	26.02
92	1332.	234.8	216.7	102.2	95.9	27.01
93	1333.	235.8	217.4	102.7	95.7	26.15
94	1334.	237.7	216.4	102.7	94.7	32.88
95	1335.	235.0	218.7	102.7	95.1	46.41
96	1336.	237.5	218.2	102.8	94.9	39.90
97	1337.	235.3	219.8	?	97.1	11.90
98	1338.	232.3	217.1	?	97.8	12.35
99	1339.	229.3	215.1	?	97.3	12.66
100	1340.	227.2	208.3	?	96.4	14.38
101	1341.	228.9	207.8	?	95.4	46.08
102	1342.	232.9	210.7	104.7	95.8	41.51
103	1343.	236.1	213.2	104.4	95.2	45.39
104	1344.	230.8	215.9	?	96.0	11.94

Notes: Min in column 1 indicates minutes past noon on the day of each test.
Time is in military format.
All temperatures are degrees Fahrenheit. To convert to degrees
Centigrade, multiply temperature (°F) - 32 by 5/9.
Oil pressure is in psig.

Day 1
M60 Tank No. 3, OE/HDO-15/40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
105	1345.	229.6	216.6	?	95.4	12.28
106	1346.	233.0	210.6	?	95.1	36.40
107	1347.	236.9	213.6	102.7	95.3	38.10
108	1348.	233.3	217.4	102.0	95.3	27.23
109	1349.	237.3	220.2	?	95.2	15.17
110	1350.	230.8	217.8	?	95.4	38.12
111	1351.	237.7	216.6	99.8	95.2	46.09
112	1352.	245.0	218.7	101.1	96.8	37.84
113	1353.	247.2	222.8	101.8	95.7	49.27
114	1354.	245.2	225.3	101.6	95.3	32.13
115	1355.	247.0	225.8	98.4	95.7	28.97
116	1356.	242.4	224.3	97.5	95.7	47.45
117	1357.	248.0	225.0	98.8	95.4	47.84
118	1358.	250.8	226.6	99.9	95.5	40.04
119	1359.	250.0	229.0	100.9	95.9	38.91
120	1400.	247.5	232.9	?	97.4	9.76
121	1401.	244.8	230.6	?	98.1	10.08
122	1402.	244.8	227.6	?	98.5	12.42
123	1403.	241.9	223.4	?	97.1	44.49
124	1404.	240.6	220.8	100.0	96.1	52.04
125	1405.	236.7	219.1	?	96.3	11.18
126	1406.	235.5	218.3	?	96.5	26.55
127	1407.	236.2	219.4	98.4	96.6	45.25
128	1408.	232.6	219.1	?	97.3	11.86
129	1409.	231.7	213.5	?	97.3	39.51
130	1410.	235.1	214.0	101.5	96.4	42.71
131	1411.	238.4	217.1	102.5	96.7	44.57
132	1412.	239.4	219.0	103.4	97.2	47.81
133	1413.	239.7	223.3	?	96.3	11.48
134	1414.	240.5	222.8	?	97.1	11.32
135	1415.	237.2	221.0	?	97.4	11.01
136	1416.	235.9	217.2	?	97.7	44.09
137	1417.	229.0	215.6	98.1	96.4	49.77
138	1418.	231.9	214.6	96.8	95.9	42.45
139	1419.	235.7	215.6	96.8	96.5	50.09
140	1420.	239.4	218.2	96.9	95.8	39.72
141	1421.	241.3	220.6	98.1	96.1	49.67
142	1422.	245.0	224.2	99.5	96.2	44.52
143	1423.	246.7	225.4	100.1	96.3	48.32
144	1424.	247.3	227.4	100.6	96.3	33.89
145	1425.	249.4	228.4	100.9	96.3	38.15
146	1426.	247.2	231.1	100.7	95.6	40.90
147	1427.	253.0	232.1	101.0	96.4	41.51
148	1428.	257.3	233.6	101.5	96.3	40.40
149	1429.	251.5	234.7	101.5	95.6	32.49

Day 2
M60 Tank No. 1, OE/HDO-40 Lubricant

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
55	1255.	114.6	132.6	?	94.9	46.25
56	1256.	116.5	133.4	103.3	93.8	45.35
57	1257.	118.2	133.7	103.6	93.8	45.00
58	1258.	126.6	135.7	102.6	94.7	58.00
59	1259.	123.5	136.5	102.7	95.2	62.16
60	1300.	136.0	137.5	102.7	94.8	40.00
61	1301.	139.3	140.7	101.9	95.4	52.91
62	1302.	146.4	147.1	100.2	95.3	60.40
63	1303.	156.3	150.3	100.8	95.2	30.38
64	1304.	91.4	149.2	102.1	95.2	28.59
65	1305.	138.7	149.3	101.2	97.4	55.37
66	1306.	164.6	157.4	98.2	98.6	53.69
67	1307.	187.6	165.2	96.9	99.2	38.85
68	1308.	177.7	169.3	97.9	99.6	47.65
69	1309.	168.8	175.7	99.0	98.4	36.90
70	1310.	190.0	179.7	97.2	98.6	33.18
71	1311.	208.9	182.7	97.6	98.8	36.04
72	1312.	205.7	185.2	97.9	99.1	43.54
73	1313.	216.0	189.2	99.2	98.7	54.35
74	1314.	210.7	193.6	100.5	99.4	58.82
75	1315.	146.8	196.3	100.2	98.6	29.42
76	1316.	217.8	201.2	99.8	99.1	38.05
77	1317.	219.9	200.6	97.5	99.8	44.88
78	1318.	228.4	203.7	97.0	100.8	50.92
79	1319.	227.5	206.5	97.4	99.8	23.37
80	1320.	220.7	209.4	?	98.7	15.22
81	1321.	218.4	207.6	?	99.2	15.78
82	1322.	216.3	205.0	?	99.3	16.13
83	1323.	213.9	201.8	?	98.4	16.63
84	1324.	211.9	199.7	?	99.8	17.34
85	1325.	210.3	199.1	?	100.4	17.77
86	1326.	217.3	193.2	?	99.9	47.17
87	1327.	217.8	199.4	99.7	99.7	40.64
88	1328.	225.5	199.6	97.4	100.4	31.44
89	1329.	230.3	201.9	97.5	99.8	56.08
90	1330.	226.7	206.0	?	99.0	15.62
91	1331.	209.8	209.6	?	98.9	29.42
92	1332.	115.9	207.8	96.1	97.3	46.82
93	1333.	238.2	207.5	96.4	98.4	49.79
94	1334.	232.4	211.1	96.5	97.8	47.75

Notes: Min in column 1 indicates minutes past noon on the day of each test.
Time is in military format.
All temperatures are degrees Fahrenheit. To convert to degrees
Centigrade, multiply temperature (°F) - 32 by 5/9.
Oil pressure is in psig.

Day 2
M60 Tank No. 1, OE/HDO-40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
95	1335.	240.5	213.0	96.2	98.1	47.01
96	1336.	240.4	215.5	95.9	98.0	39.66
97	1337.	238.7	219.6	?	97.7	13.43
98	1338.	232.1	220.1	?	98.8	13.65
99	1339.	229.1	216.4	?	99.4	14.18
100	1340.	235.7	213.2	?	98.2	42.72
101	1341.	236.7	210.5	98.0	98.6	43.21
102	1342.	240.3	212.9	98.0	99.4	46.33
103	1343.	244.5	215.9	97.6	97.8	41.71
104	1344.	247.6	218.7	97.0	98.4	47.88
105	1345.	250.4	221.1	96.7	97.8	45.13
106	1346.	246.3	220.7	96.6	97.8	31.66
107	1347.	242.4	221.0	?	97.7	12.81
108	1348.	244.7	219.7	?	98.6	31.69
109	1349.	248.5	220.3	95.3	99.0	44.29
110	1350.	247.7	223.1	95.6	97.4	41.32
111	1351.	243.5	224.8	95.8	98.0	21.91
112	1352.	239.7	223.3	98.6	100.3	41.90
113	1353.	239.2	220.4	98.3	98.8	35.88
114	1354.	237.9	219.3	99.4	99.5	45.96
115	1355.	244.8	216.6	98.3	101.3	44.66
116	1356.	248.3	220.9	99.3	100.8	41.56
117	1357.	247.3	222.5	97.9	100.1	45.84
118	1358.	247.0	223.6	98.3	101.6	40.05
119	1359.	247.1	227.4	99.2	101.9	37.58
120	1400.	251.6	223.8	98.6	102.4	38.59
121	1401.	254.3	223.9	98.2	100.3	50.55
122	1402.	250.8	225.6	97.6	99.3	26.55
123	1403.	244.8	228.5	?	99.0	12.35
124	1404.	240.0	226.3	?	98.4	12.62
125	1405.	246.1	220.4	?	98.5	43.42
126	1406.	246.6	222.1	97.0	97.8	38.86
127	1407.	248.4	221.8	96.7	97.9	41.97
128	1408.	246.1	225.7	96.6	97.3	37.05
129	1409.	251.9	223.3	97.0	99.8	43.57
130	1410.	252.5	225.1	96.3	101.0	39.22
131	1411.	249.0	225.3	97.2	98.5	39.79
132	1412.	250.8	226.9	97.2	98.6	46.51
133	1413.	254.5	227.4	96.8	98.6	36.32
134	1414.	254.7	231.3	96.7	98.6	30.00
135	1415.	253.9	228.8	96.8	98.1	43.48
136	1416.	252.2	228.1	97.2	99.0	32.92
137	1417.	254.0	227.0	96.5	99.0	36.85
138	1418.	254.3	227.8	96.2	98.4	28.84
139	1419.	250.4	227.7	96.4	98.4	47.20

Day 2
M60 Tank No. 1, OE/HDO-40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
140	1420.	248.8	228.0	97.1	98.4	43.64
141	1421.	246.7	227.4	97.1	98.0	37.68
142	1422.	246.7	224.7	97.7	98.1	43.37
143	1423.	245.1	220.3	96.9	98.7	34.22
144	1424.	241.3	222.4	?	98.7	13.09
145	1425.	237.9	221.7	?	99.2	26.40
146	1426.	235.5	218.8	100.2	99.7	23.48
147	1427.	235.5	216.3	?	98.6	19.31
148	1428.	233.8	214.5	?	99.0	13.78
149	1429.	229.7	214.6	?	100.1	22.94
150	1430.	228.8	214.2	?	100.3	17.47
151	1431.	226.1	212.6	?	100.4	23.22
152	1432.	224.1	207.4	?	99.8	39.96

Day 2
M60 Tank No. 2, OE/HDO-15/40 Lubricant

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
58	1258.	122.9	122.6	?	96.9	19.39
59	1259.	120.9	127.6	?	95.3	23.29
60	1300.	131.6	130.7	?	94.6	17.82
61	1301.	133.9	132.9	?	94.5	24.43
62	1302.	133.1	141.0	100.0	93.8	23.82
63	1303.	139.6	146.9	99.8	93.8	24.09
64	1304.	142.2	149.0	100.7	95.1	20.56
65	1305.	143.9	148.2	100.3	94.9	24.32
66	1306.	167.9	152.1	98.4	94.7	23.44
67	1307.	187.6	157.1	97.4	93.8	23.41
68	1308.	189.7	160.5	97.4	93.4	23.73
69	1309.	200.0	158.6	?	93.7	19.87
70	1310.	200.9	156.8	?	94.4	25.34
71	1311.	203.5	162.7	95.7	94.1	25.04
72	1312.	208.3	165.5	96.4	94.1	26.64
73	1313.	213.8	164.1	97.2	93.8	22.53
74	1314.	218.3	166.9	?	93.6	11.70
75	1315.	218.7	170.4	?	93.5	21.24
76	1316.	221.2	179.5	99.6	94.2	22.85
77	1317.	218.5	172.4	100.2	94.9	23.54
78	1318.	225.4	172.8	99.0	95.0	24.92
79	1319.	228.8	174.8	97.7	94.6	25.37
80	1320.	221.9	184.0	?	94.4	14.20
81	1321.	220.5	195.6	?	97.4	14.61
82	1322.	217.3	193.1	?	96.3	14.78
83	1323.	212.5	192.3	?	99.8	.545
84	1324.	210.6	191.8	?	120.3	.578
85	1325.	210.7	191.1	?	126.7	14.32
86	1326.	218.6	177.5	?	101.7	25.40
87	1327.	222.1	174.5	102.8	96.7	22.88
88	1328.	227.0	175.4	100.3	95.8	22.74
89	1329.	226.3	176.7	?	95.4	18.39
90	1330.	231.6	181.6	?	94.5	26.28
91	1331.	226.4	181.7	98.4	94.9	33.50
92	1332.	232.3	180.3	?	94.4	19.99
93	1333.	234.2	182.7	?	94.6	25.26
94	1334.	231.3	178.8	97.2	95.0	24.19
95	1335.	234.3	183.0	97.2	95.1	26.01
96	1336.	241.1	186.3	96.9	95.2	26.77
97	1337.	233.1	194.2	96.5	94.6	27.60

Notes: Min in column 1 indicates minutes past noon on the day of each test.
Time is in military format.
All temperatures are degrees Fahrenheit. To convert to degrees
Centigrade, multiply temperature (°F) - 32 by 5/9.
Oil pressure is in psig.

Day 2
M60 Tank No. 2, OE/HDO-15/40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
98	1338.	228.9	204.6	?	98.9	13.31
99	1339.	222.4	202.5	?	97.9	13.54
100	1340.	224.8	188.7	?	96.7	40.43
101	1341.	228.8	186.0	100.5	95.7	24.02
102	1342.	227.3	181.4	99.0	95.3	15.70
103	1343.	235.2	185.2	98.2	94.5	25.43
104	1344.	237.3	187.4	97.9	94.6	25.13
105	1345.	243.5	189.5	98.0	94.5	25.51
106	1346.	241.7	190.3	98.0	94.6	26.85
107	1347.	244.3	189.1	97.5	94.3	23.67
108	1348.	238.9	197.0	?	94.5	12.07
109	1349.	232.8	205.7	?	95.4	12.94
110	1350.	235.3	185.6	?	94.3	20.82
111	1351.	236.1	187.4	?	93.8	18.24
112	1352.	236.7	184.9	?	94.0	14.55
113	1353.	229.6	197.7	?	94.5	22.88
114	1354.	231.0	198.4	?	95.7	12.16
115	1355.	227.3	189.6	?	95.8	20.42
116	1356.	229.4	183.9	98.1	95.5	22.43
117	1357.	235.8	184.7	98.4	95.9	22.13
118	1358.	239.6	188.9	98.2	95.8	24.66
119	1359.	231.9	191.3	97.8	95.3	23.94
120	1400.	237.6	186.6	97.8	95.7	24.66
121	1401.	238.3	188.0	98.1	95.7	26.63
122	1402.	241.6	191.0	98.2	95.7	26.70
123	1403.	239.4	200.5	99.1	96.4	34.76
124	1404.	245.4	194.1	99.9	96.7	26.20
125	1405.	243.8	196.8	99.8	96.8	24.94
126	1406.	237.2	204.5	99.3	96.2	24.38
127	1407.	241.3	196.9	99.0	95.9	22.20
128	1408.	241.3	203.7	98.4	95.8	23.98
129	1409.	244.5	192.0	97.8	96.0	23.92
130	1410.	246.2	195.8	97.6	96.0	24.83
131	1411.	245.1	199.8	97.6	96.0	22.70
132	1412.	245.5	196.0	97.6	95.8	22.32
133	1413.	247.9	197.0	98.0	95.8	22.60
134	1414.	248.4	199.9	97.6	95.7	22.40
135	1415.	249.0	198.4	97.6	95.8	23.88
136	1416.	246.2	204.9	98.0	96.1	22.92
137	1417.	245.4	198.6	98.4	96.4	20.06
138	1418.	245.8	197.1	98.0	96.1	23.35
139	1419.	251.0	198.7	?	96.1	15.97
140	1420.	249.0	196.4	?	95.9	22.81
141	1421.	245.3	200.6	?	95.8	9.100
142	1422.	243.1	205.9	?	95.8	25.29

Day 2
M60 Tank No. 2, OE/HDO-15/40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
143	1423.	241.6	199.4	97.8	95.8	30.41
144	1424.	246.1	199.4	97.9	96.1	23.13
145	1425.	243.8	197.7	?	96.4	10.06
146	1426.	243.9	198.8	?	96.5	24.34
147	1427.	241.5	204.2	?	96.3	12.13
148	1428.	241.8	209.9	?	96.9	12.15
149	1429.	236.7	208.6	?	97.2	12.29
150	1430.	230.7	205.7	?	97.7	16.82
151	1431.	226.4	204.3	?	97.9	12.93

Day 2
M60 Tank No. 3, SAE-50 Lubricant

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
58	1258.	121.8	123.5	?	97.2	30.65
59	1259.	123.9	129.8	106.2	96.4	36.38
60	1300.	130.4	135.1	105.7	95.6	24.67
61	1301.	137.7	137.6	105.7	95.8	48.34
62	1302.	150.3	148.3	104.0	95.2	47.94
63	1303.	161.3	160.4	102.1	95.2	32.90
64	1304.	163.5	165.8	101.1	95.6	26.01
65	1305.	170.3	168.2	99.8	96.1	36.67
66	1306.	179.4	175.6	97.8	95.5	36.44
67	1307.	190.8	182.2	97.0	95.0	35.29
68	1308.	203.1	192.1	96.5	94.8	27.89
69	1309.	213.2	197.5	96.4	94.7	23.43
70	1310.	221.3	201.9	96.1	94.8	27.41
71	1311.	221.0	205.5	96.5	95.4	38.42
72	1312.	225.8	210.6	95.9	95.1	37.20
73	1313.	237.1	209.9	96.8	95.6	36.93
74	1314.	235.8	211.7	98.2	95.2	33.39
75	1315.	238.3	213.9	98.5	95.3	29.25
76	1316.	241.8	216.5	100.1	95.6	21.48
77	1317.	246.7	218.7	100.6	95.6	31.02
78	1318.	252.7	221.3	101.3	95.9	34.36
79	1319.	254.4	224.1	101.1	95.2	36.05
80	1320.	255.4	225.8	100.8	95.0	19.06
81	1321.	248.6	225.9	?	96.1	12.61
82	1322.	239.6	228.0	?	101.7	-.626
83	1323.	238.3	229.6	?	107.4	-.623
84	1324.	237.8	223.4	?	126.0	-.607
85	1325.	241.2	224.9	?	122.2	12.69
86	1326.	240.5	220.6	?	102.8	26.29
87	1327.	247.6	221.0	106.0	97.5	35.09
88	1328.	250.7	223.5	104.5	96.5	31.98
89	1329.	255.6	225.4	103.2	96.5	36.52
90	1330.	254.0	229.4	102.9	96.2	24.52
91	1331.	256.0	227.1	?	96.3	19.73
92	1332.	255.2	229.1	?	96.3	15.62
93	1333.	257.3	228.6	?	95.7	20.23
94	1334.	261.6	229.8	100.7	95.4	38.36
95	1335.	264.2	232.2	100.6	95.4	37.32
96	1336.	265.1	233.5	100.5	95.6	35.62
97	1337.	266.6	235.7	100.3	95.5	37.77

Notes: Min in column 1 indicates minutes past noon on the day of each test.
Time is in military format.
All temperatures are degrees Fahrenheit. To convert to degrees
Centigrade, multiply temperature (°F) - 32 by 5/9.
Oil pressure is in psig.

Day 2
M60 Tank No. 3, SAE-50 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
98	1338.	254.5	239.8	?	97.4	10.62
99	1339.	255.0	236.9	?	97.5	16.66
100	1340.	250.8	231.2	?	98.2	15.14
101	1341.	256.0	227.4	?	97.0	24.24
102	1342.	253.8	229.1	102.2	96.5	27.53
103	1343.	260.2	230.3	101.7	96.1	29.88
104	1344.	264.1	231.6	101.4	96.2	27.23
105	1345.	263.0	235.4	?	95.8	17.94
106	1346.	269.5	237.9	?	96.2	32.05
107	1347.	268.5	237.5	101.1	95.4	31.03
108	1348.	258.5	237.8	101.2	95.6	28.08
109	1349.	269.3	236.9	99.8	95.5	32.87
110	1350.	272.1	240.4	99.2	95.2	25.22
111	1351.	259.8	241.7	99.9	95.8	27.52
112	1352.	265.4	240.3	?	97.5	8.580
113	1353.	262.0	236.3	?	97.2	30.64
114	1354.	261.6	235.7	100.5	97.1	21.54
115	1355.	263.1	234.6	101.5	97.9	31.79
116	1356.	263.2	235.2	101.3	96.5	33.12
117	1357.	266.6	236.3	101.8	97.1	34.93
118	1358.	267.7	236.6	101.0	96.7	33.70
119	1359.	255.9	241.5	?	97.4	11.21
120	1400.	268.3	237.3	?	97.8	32.49
121	1401.	271.4	239.0	101.4	96.6	22.10
122	1402.	271.7	239.2	101.8	96.6	30.84
123	1403.	266.8	245.3	?	97.2	9.950
124	1404.	261.9	240.8	?	97.5	10.59
125	1405.	251.9	237.6	?	97.6	29.21
126	1406.	258.6	232.5	101.7	96.4	30.39
127	1407.	264.2	233.2	101.2	96.6	38.98
128	1408.	266.5	234.8	100.9	96.2	37.26
129	1409.	268.3	237.6	101.1	97.1	32.21
130	1410.	270.4	238.2	100.9	96.7	29.17
131	1411.	266.5	239.0	100.9	96.6	33.18
132	1412.	270.5	239.9	100.8	96.5	33.23
133	1413.	271.4	240.2	100.9	96.4	27.75
134	1414.	272.2	241.0	101.1	96.7	34.24
135	1415.	272.2	242.0	101.2	96.6	26.89
136	1416.	264.7	242.3	101.4	97.1	25.09
137	1417.	255.9	242.9	101.5	97.1	34.88
138	1418.	275.0	245.2	101.3	96.8	30.54
139	1419.	275.2	244.1	?	96.4	19.79
140	1420.	276.8	245.2	?	96.5	31.39
141	1421.	272.3	246.0	100.7	96.4	25.97
142	1422.	270.9	244.6	100.7	96.6	24.65

Day 2
M60 Tank No. 3, SAE-50 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
143	1423.	274.0	245.3	100.8	96.8	22.30
144	1424.	269.3	245.3	101.6	97.7	23.25
145	1425.	257.2	244.8	?	98.2	10.10
146	1426.	261.5	238.6	?	98.4	25.37
147	1427.	262.9	236.6	102.5	97.4	32.12
148	1428.	258.9	239.0	?	98.7	9.940
149	1429.	256.1	238.5	?	98.8	10.10
150	1430.	254.0	235.2	?	98.4	9.130
151	1431.	251.1	230.8	?	98.9	24.16
152	1432.	247.8	225.3	104.2	98.2	33.71
153	1433.	240.8	226.4	?	98.7	12.16

Day 3
M60 Tank No. 1, OE/HDO-15/40 Lubricant

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
43	1243.	104.1	106.2	?	92.9	30.19
44	1244.	109.5	112.4	96.4	91.5	46.12
45	1245.	110.6	118.8	98.0	92.3	56.96
46	1246.	124.6	124.1	99.2	91.2	42.75
47	1247.	125.8	125.4	100.0	91.8	42.18
48	1248.	127.2	126.6	99.7	92.0	41.30
49	1249.	128.4	127.7	98.8	92.3	40.85
50	1250.	129.7	128.7	99.8	92.3	40.07
51	1251.	130.9	129.7	100.4	92.4	39.41
52	1252.	132.0	130.5	101.2	92.7	38.69
53	1253.	133.0	131.1	101.8	92.4	38.18
54	1254.	134.0	131.7	102.0	92.8	37.82
55	1255.	134.8	132.1	102.0	92.4	37.54
56	1256.	136.3	134.6	101.7	92.1	32.89
57	1257.	142.0	135.7	101.3	92.6	28.31
58	1258.	140.6	136.5	102.0	92.8	33.44
59	1259.	140.1	136.6	102.4	93.3	33.80
60	1300.	156.3	141.5	102.4	94.0	51.23
61	1301.	163.3	150.0	102.2	95.3	54.93
62	1302.	160.7	150.3	102.0	94.5	39.36
63	1303.	160.8	153.1	102.3	94.6	25.41
64	1304.	179.8	156.6	101.3	94.6	56.86
65	1305.	190.5	165.6	101.2	96.1	54.12
66	1306.	192.9	173.3	102.0	95.9	49.81
67	1307.	204.2	178.8	101.8	97.2	37.07
68	1308.	209.4	184.5	101.8	97.5	39.84
69	1309.	211.6	189.6	101.0	96.6	40.68
70	1310.	216.1	192.7	100.4	96.7	48.20
71	1311.	218.0	195.1	100.9	97.1	54.52
72	1312.	223.2	199.5	101.7	97.6	50.63
73	1313.	228.3	202.1	102.3	97.5	40.99
74	1314.	229.3	206.4	101.8	97.8	27.27
75	1315.	233.3	208.3	101.5	97.3	36.93
76	1316.	234.6	210.5	101.2	96.7	46.97
77	1317.	236.7	211.8	100.6	98.5	25.83
78	1318.	241.9	216.2	100.9	98.2	48.16
79	1319.	242.2	216.8	100.4	97.1	32.45
80	1320.	240.5	217.7	101.2	97.7	50.92
81	1321.	243.2	217.4	101.6	99.1	46.35
82	1322.	236.6	219.4	102.2	99.1	19.30

Notes: Min in column 1 indicates minutes past noon on the day of each test.
Time is in military format.
All temperatures are degrees Fahrenheit. To convert to degrees
Centigrade, multiply temperature (°F) - 32 by 5/9.
Oil pressure is in psig.

Day 3
M60 Tank No. 1, OE/HDO-15/40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
83	1323.	249.1	222.3	102.6	99.1	45.15
84	1324.	250.5	223.8	102.1	98.4	42.78
85	1325.	248.5	225.3	102.2	97.6	22.98
86	1326.	244.9	226.0	?	98.3	11.13
87	1327.	247.8	223.0	?	98.6	43.72
88	1328.	250.9	225.5	100.1	98.4	47.42
89	1329.	248.1	224.8	100.1	97.7	44.03
90	1330.	253.5	225.2	99.6	97.6	45.92
91	1331.	255.9	228.6	99.8	98.0	39.39
92	1332.	258.5	231.3	99.9	97.6	42.50
93	1333.	262.3	231.4	100.4	98.8	31.37
94	1334.	262.6	233.4	99.5	99.9	41.12
95	1335.	265.8	234.7	99.9	99.0	43.45
96	1336.	259.2	236.6	?	98.6	10.00
97	1337.	257.2	238.0	?	98.6	10.06
98	1338.	254.4	235.4	?	98.1	10.44
99	1339.	256.4	230.2	?	97.2	42.21
100	1340.	258.9	232.5	99.3	97.7	43.08
101	1341.	258.5	233.6	98.4	98.0	42.80
102	1342.	257.5	239.7	98.6	97.6	26.49
103	1343.	255.2	238.7	100.1	98.7	22.45
104	1344.	253.7	236.5	101.6	100.2	28.65
105	1345.	248.8	232.1	100.4	99.3	33.51
106	1346.	248.6	229.7	100.7	99.2	40.00
107	1347.	251.4	227.0	100.4	98.5	33.85
108	1348.	251.0	228.7	?	99.4	10.53
109	1349.	250.6	226.3	?	100.9	39.49
110	1350.	254.5	228.5	103.1	99.3	40.75
111	1351.	257.9	231.3	103.0	100.5	38.26
112	1352.	256.6	232.5	102.1	100.1	34.57
113	1353.	255.8	236.0	100.5	99.5	35.33
114	1354.	253.3	231.4	99.8	98.6	41.10
115	1355.	255.7	232.1	?	98.9	19.72
116	1356.	253.8	234.0	?	101.7	30.09
117	1357.	257.7	232.1	101.7	101.2	39.92
118	1358.	255.6	232.8	102.1	101.0	39.30
119	1359.	259.6	234.8	?	99.9	19.45
120	1400.	263.7	236.2	?	100.3	43.05
121	1401.	263.9	238.9	102.2	99.9	37.25
122	1402.	262.5	238.1	102.6	99.8	31.55
123	1403.	258.8	238.8	?	101.0	10.00
124	1404.	255.6	236.7	?	100.3	29.09
125	1405.	255.2	232.9	100.7	99.6	46.81
126	1406.	258.3	233.0	100.3	99.5	39.93
127	1407.	258.5	234.4	99.3	99.0	40.95

Day 3
M60 Tank No. 1, OE/HDO-15/40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
128	1408.	257.2	236.6	99.8	99.8	18.30
129	1409.	251.1	233.3	?	100.9	10.59
130	1410.	248.5	231.2	?	100.8	10.82
131	1411.	246.0	228.4	?	102.0	11.22
132	1412.	243.0	225.4	?	102.2	11.52
133	1413.	239.9	222.1	?	102.1	11.93
134	1414.	236.8	218.9	?	101.8	12.40
135	1415.	233.6	215.4	?	100.3	12.78
136	1416.	230.9	211.9	?	99.5	13.22
137	1417.	228.3	208.7	?	99.6	13.68
138	1418.	225.4	205.5	?	99.7	14.17
139	1419.	222.2	202.4	?	99.1	14.63
140	1420.	218.6	199.5	?	99.3	15.09
141	1421.	215.1	196.7	?	99.6	15.60
142	1422.	211.6	193.9	?	99.5	16.13
143	1423.	208.2	191.4	99.2	99.8	16.56
144	1424.	204.9	188.7	99.0	99.9	17.14
145	1425.	202.0	186.3	98.8	99.4	17.42
146	1426.	199.1	184.1	98.6	99.7	17.98
147	1427.	202.8	182.7	99.7	99.6	49.02
148	1428.	207.7	190.0	100.7	99.6	49.59
149	1429.	214.6	192.9	99.5	98.5	50.80
150	1430.	219.9	196.7	100.0	98.3	41.53
151	1431.	228.7	202.2	99.9	98.5	44.88
152	1432.	229.8	207.1	?	98.9	39.68
153	1433.	232.6	213.2	?	98.7	16.69
154	1434.	240.0	214.7	?	99.2	45.69
155	1435.	240.4	217.6	?	99.1	37.81
156	1436.	244.1	220.3	99.6	99.3	36.45
157	1437.	250.0	222.9	99.8	99.5	41.81
158	1438.	250.4	230.5	99.8	99.8	37.77
159	1439.	248.4	231.5	100.0	99.8	36.75
160	1440.	250.4	228.9	100.1	100.1	29.19
161	1441.	252.7	229.6	101.2	100.2	23.53
162	1442.	248.3	231.0	100.8	99.8	34.87
163	1443.	249.7	229.8	100.8	99.8	41.97
164	1444.	247.0	230.7	102.3	100.4	29.57
165	1445.	247.5	227.3	?	101.1	15.64
166	1446.	248.1	227.8	?	101.2	10.67
167	1447.	245.7	224.8	?	101.8	12.66
168	1448.	243.2	227.1	?	104.8	17.53
169	1449.	241.4	223.6	?	102.1	11.55
170	1450.	237.8	221.8	?	102.0	11.96
171	1451.	236.6	215.9	?	100.5	38.31

Day 3
M60 Tank No. 2, SAE-50 Lubricant

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
56	1256.	126.7	135.3	?	95.5	39.80
57	1257.	136.7	137.1	101.9	94.4	39.15
58	1258.	135.9	139.7	101.0	94.7	38.41
59	1259.	141.0	140.5	101.2	94.8	37.50
60	1300.	154.6	145.2	101.5	95.1	57.77
61	1301.	?	149.8	101.0	94.9	58.85
62	1302.	?	152.8	101.3	95.1	60.17
63	1303.	?	153.8	101.3	94.6	27.70
64	1304.	?	156.2	101.5	94.3	57.29
65	1305.	?	160.9	100.8	94.4	57.60
66	1306.	?	167.2	100.4	94.3	56.87
67	1307.	?	173.7	101.0	95.3	59.33
68	1308.	?	177.4	100.8	94.5	24.45
69	1309.	?	182.4	100.1	94.5	56.76
70	1310.	?	187.7	99.2	94.6	51.41
71	1311.	?	188.6	98.8	94.7	55.67
72	1312.	?	190.8	98.6	94.4	56.22
73	1313.	?	195.3	98.5	94.2	55.43
74	1314.	?	198.9	99.2	94.8	44.13
75	1315.	?	199.3	99.7	94.8	46.45
76	1316.	?	198.4	99.3	94.7	47.82
77	1317.	?	200.4	99.7	95.3	52.64
78	1318.	?	202.2	99.7	95.0	51.15
79	1319.	?	204.0	99.3	94.6	53.29
80	1320.	?	205.1	99.2	94.9	45.80
81	1321.	?	208.3	99.8	95.6	45.12
82	1322.	?	208.7	101.1	96.8	46.84
83	1323.	?	212.1	102.0	97.2	51.62
84	1324.	?	212.8	102.3	96.6	51.09
85	1325.	?	214.5	102.4	96.8	46.40
86	1326.	?	216.3	102.5	97.1	45.79
87	1327.	?	216.0	?	98.3	12.16
88	1328.	?	215.2	?	96.6	34.17
89	1329.	?	218.5	99.8	96.8	53.28
90	1330.	?	217.8	99.1	96.0	48.86
91	1331.	?	217.0	98.9	96.1	48.59
92	1332.	?	220.9	99.3	96.4	44.56
93	1333.	?	222.1	99.6	96.8	43.89
94	1334.	?	222.5	100.1	97.0	50.36
95	1335.	?	222.7	100.4	96.4	50.13

Notes: Min in column 1 indicates minutes past noon on the day of each test.

Time is in military format.

All temperatures are degrees Fahrenheit. To convert to degrees Centigrade, multiply temperature (°F) - 32 by 5/9.

Oil pressure is in psig.

Day 3
M60 Tank No. 2, SAE-50 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
96	1336.	?	222.9	99.1	96.1	45.73
97	1337.	?	222.8	98.7	96.2	44.23
98	1338.	?	224.8	?	95.9	14.76
99	1339.	?	225.5	?	96.6	45.37
100	1340.	?	225.6	99.2	96.4	42.81
101	1341.	?	224.9	98.6	96.5	48.99
102	1342.	?	227.0	98.5	96.5	44.00
103	1343.	?	227.2	?	96.9	10.66
104	1344.	?	226.1	?	97.1	28.36
105	1345.	?	224.5	101.1	97.4	38.73
106	1346.	?	216.5	99.7	97.5	51.88
107	1347.	?	218.3	101.1	98.1	44.21
108	1348.	?	217.3	99.8	97.5	42.50
109	1349.	?	217.8	?	98.0	12.07
110	1350.	?	216.6	?	98.6	12.42
111	1351.	?	216.4	?	98.2	49.88
112	1352.	?	218.1	101.1	97.7	47.71
113	1353.	?	221.1	101.3	98.3	44.94
114	1354.	?	220.9	100.4	97.8	46.21
115	1355.	?	222.8	99.3	97.4	43.87
116	1356.	?	224.3	99.5	97.6	43.11
117	1357.	?	224.5	101.2	98.4	35.59
118	1358.	?	222.2	101.7	97.9	45.98
119	1359.	?	222.5	100.7	97.8	45.00
120	1400.	?	224.9	101.1	98.1	42.87
121	1401.	?	226.7	101.8	98.6	43.61
122	1402.	?	229.8	102.6	99.4	46.18
123	1403.	?	229.4	102.1	98.1	39.71
124	1404.	?	231.0	102.0	98.6	39.17
125	1405.	?	230.9	100.6	98.0	21.17
126	1406.	?	229.1	100.2	98.1	39.93
127	1407.	?	230.7	99.7	98.0	35.37
128	1408.	?	230.2	99.7	97.9	40.52
129	1409.	?	227.9	100.3	98.6	33.01
130	1410.	?	228.3	?	98.9	10.94
131	1411.	?	225.3	?	99.4	11.37
132	1412.	?	222.3	?	99.9	11.72
133	1413.	?	218.8	?	100.3	12.11
134	1414.	?	215.4	?	100.3	12.51
135	1415.	?	211.9	?	100.3	13.07
136	1416.	?	208.4	?	100.5	13.62
137	1417.	?	204.9	?	100.3	14.17
138	1418.	?	201.4	?	100.4	14.78
139	1419.	?	198.1	?	100.3	15.34
140	1420.	?	195.0	?	100.4	16.01

Day 3
M60 Tank No. 2, SAE-50 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
141	1421.	?	191.5	?	100.0	16.64
142	1422.	?	189.0	?	100.6	17.22
143	1423.	?	186.1	?	100.7	17.86
144	1424.	?	183.5	?	100.6	18.54
145	1425.	?	180.8	?	100.2	19.17
146	1426.	?	179.0	?	100.3	49.55
147	1427.	?	179.0	100.6	98.8	57.46
148	1428.	?	185.7	99.9	98.2	50.64
149	1429.	?	189.1	99.5	97.8	47.07
150	1430.	?	193.6	99.9	98.2	53.54
151	1431.	?	198.4	100.6	98.6	44.02
152	1432.	?	203.6	100.8	98.7	46.30
153	1433.	?	203.9	100.4	98.4	24.58
154	1434.	?	207.7	100.3	98.7	48.46
155	1435.	?	210.1	99.4	98.2	49.20
156	1436.	?	213.4	99.5	98.2	48.75
157	1437.	?	216.1	99.8	98.4	48.61
158	1438.	?	217.6	99.3	98.3	30.51
159	1439.	?	218.8	99.2	98.2	48.40
160	1440.	?	219.9	99.1	98.2	45.39
161	1441.	?	220.7	?	98.9	13.49
162	1442.	?	219.1	?	99.9	12.13
163	1443.	?	216.4	?	99.9	11.51
164	1444.	?	209.7	?	99.9	12.99
165	1445.	?	211.3	?	99.8	48.89
166	1446.	?	210.3	?	99.1	11.61
167	1447.	?	206.7	?	100.5	48.97
168	1448.	?	208.2	103.9	101.9	35.88
169	1449.	?	205.7	?	100.3	14.11
170	1450.	?	203.0	?	100.3	29.84
171	1451.	?	200.4	?	101.1	15.05
172	1452.	?	197.9	?	101.3	15.52
173	1453.	?	195.6	?	103.8	16.02
174	1454.	?	193.4	?	102.8	16.45
175	1455.	?	190.3	?	102.7	16.95

Day 3
M60 Tank No. 3, OE/HDO-40 Lubricant

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
56	1256.	116.1	121.4	?	92.0	25.45
57	1257.	123.8	128.8	101.2	90.6	29.75
58	1258.	122.6	132.5	100.5	91.1	30.86
59	1259.	127.1	134.9	101.7	91.5	24.52
60	1300.	140.8	142.6	102.6	92.1	37.70
61	1301.	160.1	154.7	103.1	93.2	28.68
62	1302.	149.4	160.9	102.9	92.9	25.37
63	1303.	155.7	165.5	103.1	92.2	25.70
64	1304.	171.3	169.2	103.1	91.7	30.86
65	1305.	179.0	175.2	103.3	93.3	32.03
66	1306.	194.0	184.0	103.3	92.8	35.88
67	1307.	199.8	191.1	103.3	92.8	38.59
68	1308.	210.0	195.5	?	92.3	18.78
69	1309.	214.8	199.5	?	93.5	45.20
70	1310.	221.2	202.2	102.0	93.6	27.54
71	1311.	226.8	205.0	101.2	94.1	29.37
72	1312.	232.0	208.5	101.2	93.9	28.50
73	1313.	236.0	211.7	101.1	94.0	30.52
74	1314.	235.4	213.8	101.4	94.6	29.57
75	1315.	236.5	216.0	101.3	94.5	33.13
76	1316.	240.1	215.3	101.2	92.7	29.91
77	1317.	239.3	218.7	101.1	93.8	36.58
78	1318.	243.5	218.0	101.1	93.4	31.38
79	1319.	245.7	221.0	101.0	93.8	24.75
80	1320.	250.3	222.5	101.7	93.7	35.93
81	1321.	247.9	222.4	102.4	94.5	33.48
82	1322.	249.9	224.4	103.0	94.4	33.15
83	1323.	252.1	226.0	103.5	95.4	33.09
84	1324.	247.0	228.0	103.8	94.6	27.60
85	1325.	253.6	228.4	103.5	94.5	31.08
86	1326.	235.6	234.4	?	94.9	10.41
87	1327.	241.6	234.2	?	95.0	9.76
88	1328.	249.9	227.2	?	94.3	33.13
89	1329.	256.5	227.7	102.9	94.7	39.10
90	1330.	256.4	229.0	102.8	94.6	34.90
91	1331.	258.8	230.7	102.8	94.2	21.41
92	1332.	258.1	231.0	102.8	94.3	21.70
93	1333.	266.2	233.9	102.9	95.3	23.13
94	1334.	266.2	236.4	103.1	94.9	29.08
95	1335.	267.3	238.6	102.7	95.0	24.19

Notes: Min in column 1 indicates minutes past noon on the day of each test.
Time is in military format.
All temperatures are degrees Fahrenheit. To convert to degrees
Centigrade, multiply temperature (°F) - 32 by 5/9.
Oil pressure is in psig.

Day 3
M60 Tank No. 3, OE/HDO-40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
96	1336.	274.3	241.1	101.9	94.7	36.06
97	1337.	250.7	245.5	?	96.1	8.72
98	1338.	257.2	243.3	?	96.6	8.38
99	1339.	261.0	237.1	?	96.5	25.23
100	1340.	261.8	234.4	102.6	95.0	31.69
101	1341.	265.2	236.5	102.4	95.2	21.63
102	1342.	264.3	237.3	102.3	95.1	31.19
103	1343.	260.1	238.8	103.0	95.7	24.40
104	1344.	257.8	234.3	?	96.6	10.52
105	1345.	256.2	233.2	?	96.1	28.80
106	1346.	243.5	231.9	102.4	96.3	20.09
107	1347.	253.2	231.4	103.4	97.0	30.75
108	1348.	254.7	231.4	103.4	96.2	26.44
109	1349.	252.3	231.6	104.1	98.1	29.23
110	1350.	253.9	229.6	104.9	97.4	32.43
111	1351.	253.2	231.2	105.3	97.1	35.57
112	1352.	258.1	234.9	105.2	97.1	28.06
113	1353.	251.9	232.8	103.6	97.2	28.43
114	1354.	257.8	233.9	103.3	96.5	30.72
115	1355.	256.4	234.4	103.2	96.1	29.89
116	1356.	250.6	238.2	?	98.6	9.75
117	1357.	255.6	232.2	?	98.3	32.09
118	1358.	257.3	233.8	105.1	98.6	30.77
119	1359.	260.5	235.0	104.7	97.8	31.46
120	1400.	261.8	236.2	104.8	97.8	29.16
121	1401.	265.6	237.4	104.9	98.1	36.10
122	1402.	263.3	237.8	105.1	97.3	26.83
123	1403.	241.2	244.4	?	99.8	8.78
124	1404.	254.2	242.3	?	100.4	8.10
125	1405.	257.8	235.7	?	98.2	25.70
126	1406.	259.2	234.8	104.6	97.7	29.18
127	1407.	260.3	234.5	104.0	97.4	32.73
128	1408.	262.8	234.5	103.2	97.3	33.89
129	1409.	248.4	240.0	?	98.9	9.75
130	1410.	251.4	237.6	?	99.1	10.02
131	1411.	247.7	235.1	?	99.2	10.10
132	1412.	244.4	232.0	?	99.1	10.40
133	1413.	240.4	228.9	?	99.9	10.78
134	1414.	236.8	225.5	?	99.4	11.20
135	1415.	233.2	222.3	?	99.9	11.57
136	1416.	230.0	219.1	?	99.5	11.93
137	1417.	226.3	216.0	?	99.1	12.30
138	1418.	223.1	213.0	?	99.0	12.78
139	1419.	219.8	210.0	?	98.5	13.33
140	1420.	216.7	207.3	?	99.2	13.68

Day 3
M60 Tank No. 3, OE/HDO-40 Lubricant (Cont'd)

<u>Min</u>	<u>Time</u>	<u>Sump Temp</u>	<u>Gallery Temp</u>	<u>Amb. Temp</u>	<u>Compartment Temp</u>	<u>Oil Pressure</u>
141	1421.	213.9	204.7	?	98.9	14.15
142	1422.	210.9	202.2	?	99.0	14.65
143	1423.	208.2	199.7	?	98.8	15.14
144	1424.	205.4	197.4	?	99.0	15.66
145	1425.	202.8	195.2	?	99.3	16.20
146	1426.	202.8	191.9	?	100.3	34.66
147	1427.	207.5	193.3	99.5	98.3	34.86
148	1428.	217.3	199.7	101.5	99.0	28.45
149	1429.	219.1	204.1	102.1	97.5	30.55
150	1430.	226.3	207.4	102.6	97.5	32.23
151	1431.	228.5	211.5	102.9	97.5	32.64
152	1432.	238.4	214.9	103.1	97.4	22.15
153	1433.	240.7	217.4	103.4	97.6	21.18
154	1434.	245.6	220.7	103.3	97.2	30.67
155	1435.	247.6	224.1	103.2	97.2	32.87
156	1436.	248.5	226.7	103.3	97.3	26.55
157	1437.	249.7	229.7	103.5	97.3	30.22
158	1438.	245.9	229.8	103.6	97.7	21.04
159	1439.	253.3	231.4	104.1	98.4	20.01
160	1440.	256.2	231.6	103.9	97.5	29.36
161	1441.	240.5	236.0	?	98.2	9.88
162	1442.	247.1	236.3	?	99.1	9.86
163	1443.	246.8	234.3	?	99.6	10.08
164	1444.	245.9	231.5	?	98.5	10.35
165	1445.	244.1	224.6	?	98.6	18.77
166	1446.	244.5	222.9	?	98.7	27.69
167	1447.	243.3	223.2	104.7	101.1	22.71
168	1448.	239.7	224.3	?	103.2	13.80
169	1449.	235.3	224.3	?	100.6	10.27
170	1450.	236.6	220.5	?	100.1	12.92
171	1451.	234.5	216.5	?	99.7	29.50

APPENDIX B
Lubricant Analyses

Lubricant Analyses

AL-No.	Description	XRF				Fe, ppm	Ca, %	P, %	Zn, %	S, %	D 445 K. Vis., 100°C, cSt	ICP Analyses, ppm														
		Fe	Ca	P	Zn							S	Fe	Cr	Pb	Cu	Sn	Al	Ni	Si	B	Mo	Mg	P	Zn	Ca
16544-L	OE/HDO-15/40 New	<10	0.12	0.12	0.13	0.65	13.43		3	1	<1	<1	<1	<1	9	95	<1	549	1201	1425	1425	1425				
16545-L	OE/HDO-40 New	<10	ND	0.11	0.10	0.72	15.04		4	1	8	1	1	<1	<1	5	168	<1	1823	1044	1202	22				
16546-L	SAE-50 New	<10	0.14	0.14	0.14	0.48	21.12		3	<1	1	<1	<1	<1	8	<1	11	409	1260	1359	1409	1409				
16547-L	SAE-50 Existent V1D0*	47	<0.01	0.12	0.11	0.55	19.84		50	2	12	13	<1	5	3	29	6	<1	1261	1015	1177	115				
16548-L	SAE-50 Existent V2D0	37	0.01	0.11	0.12	0.51	18.79		39	2	10	8	2	3	2	9	5	1	1140	1019	1197	234				
16549-L	SAE-50 Existent V3D0	90	0.01	0.01	0.11	0.55	21.21		100	4	24	18	<1	18	8	32	7	4	1197	1036	1266	227				
16550-L	SAE-50 Warm Up V1D1	25	0.09	0.13	0.13	0.46	20.43		17	<1	8	3	<1	<1	3	17	1	6	655	1170	1315	1007				
16551-L	OE/HDO-40 Warm Up V2D1	12	<0.01	0.10	0.11	0.62	15.68		14	<1	1	3	<1	<1	2	9	116	<1	1553	1023	1204	101				
16552-L	OE/HDO-15/40 Warm Up V3D1	30	0.01	0.11	0.13	0.59	15.00		28	<1	9	4	<1	4	3	18	71	<1	670	1140	1351	1139				
16553-L	SAE-50 Drain V1D1	19	0.09	0.11	0.13	0.49	20.92		21	<1	3	4	<1	1	2	11	1	7	641	1174	1334	1031				
16554-L	OE/HDO-40 Drain V2D1	35	<0.01	0.10	0.11	0.61	16.15		23	<1	7	4	<1	2	3	11	108	<1	1518	1031	1166	131				
16555-L	OE/HDO-15/40 Drain V3D1	30	0.10	0.11	0.12	0.60	15.05		34	1	14	5	<1	3	1	21	69	<1	702	1173	1360	1114				
16556-L	OE/HDO-40 Drain V1D2	33	0.02	0.10	0.11	0.60	16.96		22	<1	<1	3	<1	<1	1	26	96	3	1281	1088	1240	427				
16557-L	OE/HDO-15/40 Drain V2D2	20	0.08	0.12	0.13	0.66	14.11		19	<1	2	2	2	1	<1	10	97	<1	930	1115	1327	895				
16558-L	SAE-50 Drain V3D2	30	0.11	0.12	0.13	0.55	17.14		30	1	<1	4	<1	4	<1	14	39	5	580	1208	1367	1212				
16559-L	OE/HDO-15/40 Drain V1D3	20	0.11	0.12	0.13	0.64	14.30		12	<1	<1	2	<1	2	<1	13	93	<1	764	1146	1363	1106				
16560-L	SAE-50 Drain V2D3	19	0.11	0.13	0.13	0.57	16.96		15	<1	<1	2	<1	<1	<1	9	49	6	667	1182	1329	1149				
16561-L	OE/HDO-40 Drain V3D3	27	0.06	0.08	0.13	0.60	17.06		21	<1	9	3	<1	1	<1	10	75	2	985	1160	1267	801				

* V indicates vehicle number and D indicates day of test sequence.

DISTRIBUTION LIST

DEPARTMENT OF DEFENSE

DEFENSE TECHNICAL INFORMATION CTR
CAMERON STATION 12
ALEXANDRIA VA 22314

DEPT OF DEFENSE
OASD/P&L
ATTN: L/EP (MR DYCKMAN) 1
WASHINGTON DC 20301-8000

CDR
DEFENSE GENERAL SUPPLY CTR
ATTN: DGSC-SSM 1
ATTN: DGSC-STC 1
RICHMOND VA 23297-5000

DOD
ATTN: DUSDRE (RAT) (DR DIX) 1
ROOM 3-D-1089, PENTAGON
WASHINGTON DC 20301

DEPARTMENT OF THE ARMY

CDR
US ARMY BELVOIR RESEARCH,
DEVELOPMENT & ENGINEERING CTR
ATTN: STRBE-VF 10
STRBE-BT 2
FORT BELVOIR VA 22060-5606

HQ, DEPT OF ARMY
ATTN: DALO-TSE 1
DALO-TSZ-B (MR KOWALCZYK) 1
DALO-PLA (DR WILTSHIRE) 1
SARD-TR (MS VANNUCCI) 1
WASHINGTON DC 20310-0561

CDR
US ARMY MATERIEL COMMAND
ATTN: AMCDE-SS 1
AMCSM-SP 1
AMCDE-WH 1
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

DIRECTOR
AVIATION APPLIED TECH DIR
US ARMY R&T ACTIVITIES (AVSCOM)
ATTN: SAVRT-TY-ATP (MR MORROW) 1
FORT EUSTIS VA 23604-5577

CDR
US ARMY TANK-AUTOMOTIVE COMMAND
ATTN: AMSTA-RG (MR CHECKLICK) 1
AMSTA-TSL (MR BURG) 1
AMSTA-MTC (MR GAGLIO) 1
AMSTA-RGP (MR RAGGIO) 1
AMSTA-MLF (MR KELLER) 1
AMSTA-MC 1
AMSTA-MV 1
AMSTA-Z (MR FARKUS) 1
WARREN MI 48397-5000

DIRECTOR
US ARMY AVIATION RESEARCH &
TECHNOLOGY ACTIVITIES (AVSCOM)
ATTN: SAVRT-R (MR ANDRE) 1
AMES RESEARCH CENTER
(MAIL STOP 207-5)
MOFFETT FIELD CA 94035-1099

DIRECTOR
US ARMY MATERIEL SYSTEMS
ANALYSIS ACTIVITY
ATTN: AMXSY-CM 1
ABERDEEN PROVING GROUND MD
21005-5006

CDR
THEATER ARMY MATERIAL MGMT
CENTER (200TH)-DPGM
DIRECTORATE FOR PETROL MGMT
ATTN: AEAGD-MMC-PT-Q 1
APO NY 09052

PROJ MGR, MOBILE ELECTRIC POWER
ATTN: AMCPM-MEP-TM 1
(COL BRAMLETTE)
7500 BACKLICK ROAD
SPRINGFIELD VA 22150

CDR
US ARMY GENERAL MATERIAL &
PETROLEUM ACTIVITY
ATTN: STRGP-F (MR ASHBROOK) 1
STRGP-FE, BLDG 85-3
(MR GARY SMITH) 1
STRGP-FT (MR ROBERTS) 1
NEW CUMBERLAND PA 17070-5008

HQ
US ARMY ARMAMENT, MUNITIONS,
AND CHEMICALS COMMAND
ATTN: AMSAR-LEM 1
ROCK ISLAND ARSENAL IL 61299-6000

CDR
US ARMY ARMAMENT RSCH, DEVEL &
ENGRG CENTER
ATTN: SMCAR-LC
SMCAR-SC
SMCAR-ESC-S
PICATINNY ARSENAL NJ 07806-5000

CDR
US ARMY WATERVLIET ARSENAL
ATTN: SARWY-RDD
WATERVLIET NY 12189

CDR
US ARMY FORCES COMMAND
ATTN: FCSJ-SA
FORT MCPHERSON GA 30330-6000

CDR
US ARMY RES, DEV & STDZN GROUP (UK)
ATTN: AMXSN-UK-RA
(DR REICHENBACH)
BOX 65
FPO NEW YORK 09510-1500

CDR, US ARMY TROOP SUPPORT
COMMAND
ATTN: AMSTR-ME
AMSTR-S
AMSTR-E (MR CHRISTENSEN)
AMSTR-WL
4300 GOODFELLOW BLVD
ST LOUIS MO 63120-1798

CDR
US ARMY LABORATORY COMMAND
ATTN: AMSLC-TP-PB (MR GAUL)
AMSLC-TP-AL
ADELPHI MD 20783-1145

CDR
US ARMY DEPOT SYSTEMS COMMAND
ATTN: AMSDS-RM-EFO
CHAMBERSBURG PA 17201

CDR, US ARMY AVIATION SYSTEMS CMD
ATTN: AMSAV-EP
4300 GOODFELLOW BLVD
ST LOUIS MO 63120-1798

CDR
US ARMY YUMA PROVING GROUND
ATTN: STEYP-MT-TL-M
(MR DOEBBLER)
YUMA AZ 85364-9130

CDR
US ARMY TANK-AUTOMOTIVE CMD
PROGR EXEC OFF CLOSE COMBAT
PM ABRAMS, ATTN: AMCPM-ABMS
PM BFVS, ATTN: AMCPM-BFVS
PM 113 FOV, ATTN: AMCPM-M113
PM M60 FOV, ATTN: AMCPM-M60
APEO SYSTEMS, ATTN: AMCPEO-CCV-S
PM LAV, ATTN: AMCPM-LA-E
WARREN MI 40397-5000

CDR
US ARMY RESEARCH OFFICE
ATTN: SLCRO-EG (DR MANN)
P O BOX 12211
RSCH TRIANGLE PARK NC 27709-2211

CDR
US ARMY TANK-AUTOMOTIVE CMD
PROGR EXEC OFF COMBAT SUPPORT
PM LIGHT TACTICAL VEHICLES
ATTN: AMCPM-TVL
PM MEDIUM TACTICAL VEHICLES
ATTN: AMCPM-TVM
PM HEAVY TACTICAL VEHICLES
ATTN: AMCPM-TVH
WARREN MI 40397-5000

PROGRAM EXECUTIVE OFFICE, TROOP
SUPPORT
DEPUTY FOR SYSTEMS MGMT
ATTN: AMCEPO-TRP
ST LOUIS MO 63120-1798

CDR
CHEMICAL RD&E CENTER
ATTN: SMCCR-MUS
ABERDEEN PROVING GRD MD
21010-5423

PROJ OFF, AMPHIBIOUS AND WATER
CRAFT
ATTN: AMCPM-AWC-R
4300 GOODFELLOW BLVD
ST LOUIS MO 63120-1798

CDR
US ARMY FOREIGN SCIENCE & TECH
CENTER
ATTN: AIAST-RA-ST3 (MR BUSI)
FEDERAL BLDG
CHARLOTTESVILLE VA 22901

DIR
AMC PACKAGING, STORAGE, AND
CONTAINERIZATION CTR
ATTN: SDSTO-TE-S
TOBYHANNA PA 18466-5097

CDR
US ARMY LEA
ATTN: DALO-LEP
NEW CUMBERLAND ARMY DEPOT
NEW CUMBERLAND PA 17070

CDR
US ARMY GENERAL MATERIAL &
PETROLEUM ACTIVITY
ATTN: STRGP-PW
BLDG 247, DEFENSE DEPOT TRACY
TRACY CA 95376-5051

CDR
AMC MATERIEL READINESS SUPPORT
ACTIVITY (MRSA)
ATTN: AMXMD-MO (MR BROWN)
LEXINGTON KY 40511-5101

CDR
US ARMY ORDNANCE CENTER &
SCHOOL
ATTN: ATSL-CD-CS
ABERDEEN PROVING GROUND MD
21005-5006

CDR
US ARMY ENGINEER SCHOOL
ATTN: ATSE-CD
LEONARD WOOD MO 65473-5000

HQ, US ARMY T&E COMMAND
ATTN: AMSTE-CM-R-O
AMSTE-TE-T
ABERDEEN PROVING GROUND MD
21005-5006

CDR
CONSTRUCTION ENG RSCH LAB
ATTN: CERL-ES
P O BOX 4005
CHAMPAIGN IL 61820

HQ, US ARMY ARMOR CENTER
ATTN: ATSB-CD-ML
ATSB-TSM-T
FORT KNOX KY 40121

CDR
US ARMY QUARTERMASTER SCHOOL
ATTN: ATSM-CDM
ATSM-LL FSD
FORT LEE VA 23801

DIRECTOR
US ARMY RSCH & TECH ACTIVITIES
(AVSCOM)
PROPULSION DIRECTORATE
ATTN: SAVRT-PL-C (MR ACURIO)
21000 BROOKPARK ROAD
CLEVELAND OH 44135-3127

PROJECT MANAGER
PETROLEUM & WATER LOGISTICS
ATTN: AMCPM-PWL
4300 GOODFELLOW BLVD
ST LOUIS MO 63120-1798

CDR
COMBINED ARMS COMBAT
DEVELOPMENT ACTIVITY
ATTN: ATZL-CAT-E
FORT LEAVENWORTH KS 66627-5300

CDR
US ARMY LOGISTICS CTR
ATTN: ATCL-CD
ATCL-MS
FORT LEE VA 23801-6000

HQ
US ARMY TRAINING & DOCTRINE CMD
ATTN: ATCD-SL
FORT MONROE VA 23651-5000

CDR
US ARMY TRANSPORTATION SCHOOL
ATTN: ATSP-CD-MS
FORT EUSTIS VA 23604-5000

CDR
US ARMY FIELD ARTILLERY SCHOOL
ATTN: ATSF-CD
FORT SILL OK 73503-5600

CDR
US ARMY INFANTRY SCHOOL
ATTN: ATSH-CD-MS-M
ATSH-TSM-FVS
FORT BENNING GA 31905-5400

DIR
US ARMY MATERIALS TECHNOLOGY
LABORATORY
ATTN: SLCMT-MCM-P (DR FOPIANO) 1
WATERTOWN MA 02172-2796

CDR
US ARMY MEDICAL R&D LABORATORY
ATTN: SGRD-USG-M (MR EATON) 1
FORT DETRICK, MD 21701

CDR
US ARMY SAFETY CENTER
ATTN: PESD-SSD 1
FORT RUCKER AL 36362

DEPARTMENT OF THE NAVY

CDR
NAVAL AIR PROPULSION CENTER
ATTN: PE-32 (MR MANGIONE) 1
P O BOX 7176
TRENTON NJ 06828-0176

JOINT OIL ANALYSIS PROGRAM -
TECHNICAL SUPPORT CTR 1
BLDG 780
NAVAL AIR STATION
PENSACOLA FL 32508-5300

CDR
DAVID TAYLOR RESEARCH CTR
ATTN: CODE 2830 (MR SINGERMAN) 1
CODE 2831
ANNAPOLIS MD 21402-5067

PROJ MGR, M60 TANK DEVELOPMENT
ATTN: USMC-LNO 1
US ARMY TANK-AUTOMOTIVE
COMMAND (TACOM)
WARREN MI 48397-5000

CDR
NAVAL FACILITIES ENGR CTR
ATTN: CODE 1202B (MR R BURRIS) 1
200 STOVAL ST
ALEXANDRIA VA 22322

CDR
NAVY PETROLEUM OFFICE
ATTN: CODE 43 (MR LONG) 1
CAMERON STATION
ALEXANDRIA VA 22304-6180

CDR
3RD TANK BATTALION
7TH MARINE EXPEDITIONARY BRIGADE
ATTN: FMF 2
TWENTY-NINE PALMS CA 92278-5525

CDR
NAVAL SEA SYSTEMS COMMAND
ATTN: CODE 05M32 1
WASHINGTON DC 20362-5101

DEPARTMENT OF THE NAVY
HQ, US MARINE CORPS
ATTN: LMM/2 1
WASHINGTON DC 20380

CDR
NAVAL AIR SYSTEMS COMMAND
ATTN: CODE 53632F (MR MEARNES) 1
WASHINGTON DC 20361-5360

CDR
NAVAL RESEARCH LABORATORY
ATTN: CODE 6170 1
WASHINGTON DC 20375-5000

CDR
NAVAL AIR DEVELOPMENT CTR
ATTN: CODE 6061 1
WARMINSTER PA 18974-5000

OFFICE OF THE CHIEF OF NAVAL
RESEARCH
ATTN: OCNR-126 (DR ROBERTS) 1
ARLINGTON VA 22217-5000

DEPUTY CG
USMC RDA COMMAND
ATTN: CBAT 1
QUANTICO VA 22134

DEPARTMENT OF THE AIR FORCE

HQ AIR FORCE SYSTEMS COMMAND
ATTN: AFSC/DLF (DR DUES) 1
ANDREWS AFB MD 20334

CDR
US AIR FORCE WRIGHT AERO LAB
ATTN: AFWAL/POSL (MR JONES) 1
AFWAL/MLBT (MR SNYDER) 1
WRIGHT-PATTERSON AFB OH
45433-6563

CDR

SAN ANTONIO AIR LOGISTICS CTR

ATTN: SAALC/SFT (MR MAKRIS)
SAALC/MMPRR

KELLY AIR FORCE BASE TX 78241

CDR

WARNER ROBINS AIR LOGISTIC CTR

ATTN: WRALC/MMVR-1
(MR PERAZZOLA)

ROBINS AFB GA 31098

OTHER GOVERNMENT AGENCIES

1 NATIONAL AERONAUTICS AND SPACE
1 ADMINISTRATION 1
LEWIS RESEARCH CENTER
CLEVELAND OH 44135

US DEPARTMENT OF ENERGY
ATTN: MR ECKLUND 1
1 MAIL CODE CE-151
FORRESTAL BLDG.
1000 INDEPENDENCE AVE, SW
WASHINGTON DC 20585